Environmental Protection Agency

- (ii) Performing maintenance inside a temporary enclosure and use a vacuum system either equipped with a filter rated by the manufacturer to achieve a capture efficiency of 99.97 percent for 0.3 micron particles or routed to an existing control device permitted for this activity.
- (iii) Performing maintenance inside a partial enclosure and use of wet suppression sufficient to prevent dust formation.
- (iv) Decontamination of equipment prior to removal from an enclosure.
- (v) Immediate repair of ductwork or structure leaks without an enclosure if the time to construct a temporary enclosure would exceed the time to make a temporary or permanent repair, or if construction of an enclosure would cause a higher level of emissions than if an enclosure were not constructed.
- (vi) Activities required for inspection of fabric filters and maintenance of filters that are in need of removal and replacement are not required to be conducted inside of total enclosures. Used fabric filters must be placed in sealed plastic bags or containers prior to removal from a baghouse.
- (7) Material transport. You must collect and transport all lead bearing dust (i.e. lead bearing material which is a dust) within closed conveyor systems or in sealed, leak-proof containers unless the collection and transport activities are contained within a total enclosure. All other lead bearing material must be contained and covered for transport outside of a total enclosure in a manner that prevents spillage or dust formation. Intact batteries and lead ingot product are exempt from the requirement to be covered for transport.
- (d) Your standard operating procedures manual must specify that records be maintained of all pavement cleaning, vehicle washing, and battery storage inspection activities performed to control fugitive dust emissions.
- (e) You must pave all grounds on the facility or plant groundcover sufficient to prevent wind-blown dust. You may use dust suppressants on unpaved areas that will not support a groundcover (e.g., roadway shoulders, steep slopes, limited access and limited use roadways).

(f) As provided in §63.6(g), as an alternative to the requirements specified in this section, you can demonstrate to the Administrator (or delegated State, local, or Tribal authority) that an alternative measure(s) is equivalent or better than a practice(s) described in this section.

§63.546 Compliance dates.

- (a) For affected sources that commenced construction or reconstruction on or before May 19, 2011, you must demonstrate compliance with the requirements of this subpart no later than January 6, 2014.
- (b) For affected sources that commenced construction or reconstruction after May 19, 2011, you must demonstrate compliance with the requirements of this subpart by January 5, 2012 or upon startup of operations, whichever is later.
- (c) Until the date specified in 63.546(a), secondary lead smelters that commenced construction or reconstruction on or before May 19, 2011, must continue to demonstrate compliance with the requirements of this subpart, codified in 40 CFR 63.541 through 40 CFR 63.550, that were in effect prior to the January 5, 2012, amendments. This means that secondary lead smelters that commenced construction or reconstruction on or before June 9, 1994, must continue to demonstrate compliance with existing source requirements of this subpart that were in effect prior to the January 5, 2012, amendments until the date specified in §63.546(a). Secondary lead smelters that commenced construction or reconstruction after June 9, 1994, and on or before May 19, 2011, must continue to demonstrate compliance with new source requirements of this subpart that were in effect prior to the January 5, 2012, amendments until the date specified in §63.546(a).

[77 FR 580, Jan. 5, 2012, as amended at 79 FR 371, Jan. 3, 2014]

§ 63.547 Test methods.

(a) You must use the test methods from appendix A of part 60 as listed in paragraphs (a)(1) through (5) of this section to determine compliance with the emissions standards for lead compounds specified in §63.543(a) and (b).